













| SPECIFICATIO | NS |
|-----------------------------|--|
| Capacity | 9" / 23 cm Wheel |
| Spindle | %" - 11 Threaded |
| Circuit Type Open Center | |
| Flow Range | 4-12 gpm / 15-45 lpm |
| Working Pressure | 1000-2000 psi / 70-140 bar |
| Full Relief Setting | 2250 psi / 155 bar |
| RPM | 3200 @ 12 gpm / 45 lpm |
| Weight (with guard) | 15 lbs / 6.8 kg |
| Length | 11" / 28 cm |
| Width (with guard) | 10¼" / 26 cm |
| Hydraulic Ports | -8 SAE O-ring |
| Connection Size and Type | %" Male Pipe Adapter |
| Couplers | Varies with model (See Ordering Information) |
| Hose Whips | No (See Accessories) |

FEATURES

- Integral Stanley Hyrevz gear motor produces high torque
- Stainless Steel spools and fasteners
- · Two position assist handle for right/left hand operation
- · Oversized trigger with guard for diver comfort
- Adjustable wheel guard for infinite positions
- · Plastisol covered handle for comfortable ergonomic grip
- Use with grinding wheels, hull scrubbing brushes, wire and nylon brushes, barnacle busters and Desmond wheels

3200 rpm @ 12 gpm

Cast-in lifting eye

















ORDERING INFORMATION

PART NUMBER


GR29310 Grinder, Underwater, less couplers GR2930101 Grinder, Underwater, couplers, CE

| ACCE | SSORIES |
|-------|--|
| 03971 | Flush-Face Coupling Set, %" NPT |
| 03974 | Flush-Face Coupling Set, ½" NPT |
| 06830 | Hose Whip 18" long, -8 SAE x 1/2" NPT |
| 02587 | Grinding wheel for metal, 9" diameter x % - 11 thd |
| 02588 | Grinding wheel for masonry, 9" diameter x % - 11 thd |
| 03691 | Grinding wheel, 7" diameter x 1/8 - 11 thread |
| 05194 | Adapter, % - 11 thread, depressed center wheel |
| 31848 | Dual Hose, 50' x ½", with couplers |
| 31972 | Dual Hose, 25' x ½", with couplers |
| 58633 | Twinned Hose, 25' x 1/2", with couplers |
| 58634 | Twinned Hose, 50' x 1/2", with couplers |

When hydraulic hose exceeds 100' (30.4 m) in length, increase I.D. of both pressure and return hose. For more information, consult Stanley Hydraulic Tools.

MPORTANT

To fill out a Product Warranty Recording form and for information on your warranty visit stanleyhydraulic.com and select the Warranty tab.



Note: The warranty recording form must be submitted to validate the warranty.

















| | 9" All-Cut Diamond Gri | 9" All-Cut Diamond Grit Cutting Disc | | |
|--|---|---|--|--|
| Description Application Materials Part Numb Size Max Rating | General Cutting / Various All Purpose, Concrete, Sto AC230-22 230mm x 3.1mm | 230mm x 3.1mm | | |
| | 9" All-Grind Diamond G | Grit Grinding Disc | | |
| Description Application Materials Part Numb Size Max Rating | General Grinding / Various All Purpose, Concrete, Sto AG230-22 230mm DPC | Durable, Long Life with ability to grind wide range of materials General Grinding / Various Materials All Purpose, Concrete, Stone, Steel & Alloys, Composite, PVC, Wood AG230-22 230mm DPC | | |
| | 7" & 9" Diamond Cuttir | ng Disc DT 600 U | | |
| Description Application Materials Part Numb Size Max Rating | Cutting Concrete, Sandstone, Con 322633 180mm x 2.6mm | Top Performance, long life Cutting Concrete, Sandstone, Construction Materials 322633 322634 180mm x 2.6mm 230mm x 2.6mm | | |
| | 7" & 9" Diameter Bond | 7" & 9" Diameter Bonded Abrasive Grinding Disc for Metal | | |
| Description Application Materials Part Numb Size Max Rating | Grinding Pipe, Structural, Steel, Stainless steel GW778DCS 180mm DPC x 6.4mm | GW778DCS GW978DCS 180mm DPC x 6.4mm 230mm DPC x 6.4mm | | |
| | 7" & 9" Diameter Bond | 7" & 9" Diameter Bonded Abrasive Cutting Disc for Metal | | |
| Description Application Materials Part Numb Size Max Rating | Cutting Pipe, Structural, So Steel, Stainless steel CW778DCS 180mm x 2.5mm | erformance, minimal vibration & long life olid and Plate CW978DCS 230mm DPC x 2.5mm 6,600rpm (80 m/s) | TO THE RESERVE TO THE | |













| | | 7" & 9" Diameter Bonde | ed Abrasive Grinding Disc for Stone | |
|---|---|---|-------------------------------------|---|
| • | Description Application Materials Part Number | Depressed Centre High performance, minimal vibration & long life Grinding Masonry, Stone, Concrete Stone, Brick, Concrete, Ceramics GW778DCM GW978DCM | | |
| • | Size | 180mm DPC x 6.4mm | 230mm DPC x 6.4mm | P. Side Co. Blatton - Stone Stein - Mathematica |
| • | Max Rating | 8,500rpm (80 m/s) | 6,600rpm (80 m/s) | Perdin - Karman Ko - German |
| | | 9" Diameter Bonded Ab | rasive Cutting Disc for Stone | |
| • | Description Application Materials Part Number Size Max Rating | Depressed Centre High performance, minimal vibration & long life Cutting Masonry, Stone, Concrete Stone, Brick, Concrete, Ceramics CW978DCM 230mm DPC x 3.2mm 6,600rpm (80 m/s) | | |
| | | 9" Diameter Bonded Abrasive Grinding Disc for Metal | | |
| • | Description | 5/8-11 thread Spin-On Excellent material removal and long life | | |
| • | Application | Grinding Pipe, Structural, S | olid and Plate | men angle and a first process |
| • | Materials | Steel, Stainless Steel | | |
| • | Part Number | GW49105S | | |
| • | Size Max Rating | 230mm x 6mm x 5/8-11 6,600rpm (80 m/s) | | |
| • | IVIAX NALIIIG | 0,0001pm (00 m/ 3) | | |
| | | | rasive Cutting Disc for Metal | |
| | | 5/8-11 thread Spin-On | | |
| • | Description | Excellent material removal and long life | | |
| • | Application Materials | Cutting Pipe, Structural, Solid and Plate | | |
| • | Part Number | Steel , Stainless Steel | | |
| • | Size | CW48983S 230mm x 4mm x 5/8-11 | | |
| • | Max Rating | 6,600rpm (80 m/s) | | |
| | | | | |















| | | Cup Wire Brush 125mm Crimped Steel Bristles | |
|---|-------------|--|--|
| • | Description | General purpose cup wire brush | |
| • | Application | Surface preparation, Rust removal, Cleaning | |
| • | Materials | Various, Inc: Steel, Stainless Steel & Glass Fibre | |
| • | Part Number | CWB125-CB58 | NAME OF THE OWNER, OF THE OWNER, OF THE OWNER, OF THE OWNER, OWNER, OWNER, OWNER, OWNER, OWNER, OWNER, OWNER, |
| • | Size | 125mm x 5/8-11 threaded bore | |
| • | Max Rating | 6,500rpm | |
| | | Cup Wire Brush 100mm Twisted Knot Steel Bristles | |
| | | | 0 |
| • | Description | Hard wearing cup brush with good material removal | CII |
| • | Application | De-burring, De-scaling, Marine growth removal, Paint removal | |
| • | Materials | Various, Inc: Steel, Stainless Steel & Glass Fibre | |
| • | Part Number | CWB100-TK58 | THE OWNER OF THE OWNER |
| • | Size | 100mm x 5/8-11 threaded bore | 4. 医复数动力 |
| • | Max Rating | 8,500rpm | |
| | | Bevel Wire Brush 115mm Twisted Knot Steel Bristles | |
| | | | K Bara |
| • | Description | Hard wearing bevel brush with good material removal | |
| • | Application | De-burring, De-scaling, Marine growth removal, Paint removal | |
| • | Materials | Various, Inc: Steel, Stainless Steel & Glass Fibre | PART |
| • | Part Number | BWB115-TK58 | |
| • | Size | 115mm x 5/8-11 threaded bore | AND THE PROPERTY OF THE PROPER |
| • | Max Rating | 12,500rpm | |
| | | Nylon Brush 160mm | |
| | Danadatian | | |
| • | Description | Nylon Brush | |
| • | Application | Marine growth removal, Cleaning & Polishing | 7 |
| • | Materials | Various, Inc: Steel, Stainless Steel & Glass Fibre NB160 | |
| • | Part Number | 160mm | |
| • | Size | 3,200rpm (44 m/s) | |
| • | Max Rating | Adaptor for NB160 Nylon Rotary Brush | |
| | | Adaptor for Notary Brush | |
| • | Description | Aluminium mount for rotary nylon brush | |
| • | Application | Adaptor for NB160 (above) | |
| • | Part Number | NB160ADP | |
| • | Size | 5/8-11 threaded bore | |
| | | | |

















| | | 7" Rapid Strip Disc DPC, Xtra Coarse, Long Lasting | | | |
|---|---|--|-----------------------|---------|--------------|
| • | Description Application Materials Part Number Size Max Rating | Synthetic fibres and coarse ceramic alumina grain Rust & Paint removal. Surface Preparation Various, Inc. Steel, Stainless Steel & Glass Fibre RSD03920 180mm DPC 8,000rpm (75 m/s) | | | |
| | J | 7" Rapid Strip Disc I | OPC, Xtra Coarse, STD | Density | and the same |
| • | Description Application Materials Part Number Size Max Rating | Synthetic fibres and coarse silicon carbide grains Light Marine Growth, Rust & Paint removal. Surface Preparation Various, Inc. Steel, Stainless Steel & Glass Fibre RSD85750 180mm DPC 6,700rpm (63 m/s) | | | |
| | /// | 7" Rapid Strip Disc DPC, Xtra Coarse, Harder Density | | | |
| • | Description Application Materials Part Number Size Max Rating | Synthetic fibres and coarse silicon carbide grains Light Marine Growth, Rust & Paint removal. Surface Preparation Various, Inc. Steel, Stainless Steel & Glass Fibre RSD09586 180mm DPC 8,000rpm (75 m/s) | | | |
| | | 7" Conical Fibre Disc (40/80/120 Grit) DPC | | | |
| • | Description Application Materials Part Number Size Grit | Zirconium, excellent material removal and long life Ideal for edge grinding, surface preparation & Cleaning, De-rusting Steel, Stainless steel CFD02341 CFD02345 CFD02347 180mm DPC 180mm DPC 40-Grit 80-Grit 120-Grit | | | |
| • | Max Rating | 8,500rpm (80 m/s) 8,500rpm (80 m/s) 8,500rpm (80 m/s) | | | |

















| SPECIFICATIONS | | |
|--------------------|--------------------|--|
| Outside Diameter | 150mm (6") | |
| Recommended Speed | 1,000 to 2,000 rpm | |
| Max Rated Speed | 3,200 rpm | |
| Fitting | 5/8-11 Arbour | |
| Cutting Heads | 7 per unit | |
| Main Body Material | Stainless Steel | |

Features and Benefits

Removes heavy build-up of mussels, barnacles or other encrustations from steel, concrete, pilings, seawalls, bulkheads and ships easily.

It is a stainless steel one piece aircraft quality housing stainless steel blocks on the outside diameter and fits a 5/8"-11 shaft. (Other fittings and mounts also available).

Furnished with sharp tooth toolsteel cutters as standard, with builtin safety guard and balanced design for easy operation.

As the unit moves across the surface, the outside blocks shatter barnacles and other heavy growth. The rotating hardened steel cutters follow up with a chipping and scraping action which removes the

remaining material, leaving a clean surface. Water passing through the tool keeps the cutting wheels clean

The rotary action displaces water thus creating a vacuum under the unit. This results in the unit being pressed and held against the ship or work surface. Slight pressure on either side of the tool allows the operator to guide it in any direction.

The tool is ecologically safe since it adds no harmful chemicals to our environment.

A speed of 1000 rpm to 2000 rpm is suggested for underwater use. See over page for hydraulic flow vs shaft speed graph.

Applications include:

Paint removal Ship hulls & rudders Offshore wind turbines **Bridges Pilings** Marine structures Harbour structures Storage tanks















ORDERING INFORMATION

MODEL/PART No. DESCRIPTION

HOP50830

Barnacle Basher 150mm (6") Heavy duty unit with quick change cutter sets

All tools and their associated parts are

warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. We reserve the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty becomes void if maximum flow and


pressure ratings are exceeded.

WARRANTY

ACCESSORIES

| PART No. | DESCRIPTION |
|----------|---|
| 50631 | Quick Change Cutter Set for 50830 Unit (Set of 7) |
| 50684 | Axles (Set of 7) for all 150mm (6") Units |

GR29 Hydraulic Flow Vs Shaft Speed
































| ITEM# | PART # | QTY | DESCRIPTION |
|-------|--------|-----|---|
| 1 | 00026 | 1 | O-RING * |
| 2 | 00166 | 2 | RETAINING RING |
| 3 | 00230 | 4 | CAPSCREW |
| 4 | 00231 | 2 | LOCKWASHER |
| 5 | 00285 | 1 | ROLL PIN |
| 6 | 00580 | 1 | SETSCREW |
| 7 | 00599 | 1 | SETSCREW (GR2930101 ONLY) |
| 8 | 00672 | 1 | RETAINING RING EXTERNAL |
| 9 | 00786 | 1 | CAPSCREW |
| 10 | 00936 | 2 | ADAPTER |
| 11 | 01211 | 2 | O-RING * |
| 12 | 01220 | 1 | GREASE FITTING 1/8 CAPPED |
| 13 | 01870 | 8 | CAPSCREW |
| 14 | 03972 | 1 | COUPLER,3/8FEM. 3/8NPT FL.FACE SET 03971 |
| 15 | 03973 | 1 | COUPLER,3/8MALE 3/8NPT FL.FACE SET 03971 |
| 16 | 06533 | 1 | O-RING * |
| 17 | 07724 | 2 | NYLOCK NUT |
| 18 | 07987 | 1 | BACK-UP WASHER |
| 19 | 07988 | 1 | COMPRESSION COIL SPRING |
| 20 | 07989 | 1 | IDLER GEAR ASSY (INCLUDES DU BUSHING) |
| 21 | 07991 | 1 | IDLER SHAFT |
| 22 | 08002 | 1 | REVERSING SPOOL |
| 23 | 08015 | 2 | BACK-UP RING * |
| 24 | 08017 | 1 | O-RING * |
| 25 | 08023 | 1 | O-RING * |
| 26 | 08130 | 1 | HANDLE |
| 27 | 09275 | 1 | RETAINING RING EXTERNAL |
| 28 | 09396 | 1 | BACK-UP RING * |
| 29 | 11206 | 1 | CIRCUIT TYPE "C" STICKER |
| 30 | 11937 | 1 | WHEEL GUARD |
| | 08322 | 1 | WHEEL GUARD U/W MODEL |
| 31 | 12283 | 1 | TRIGGER U/W |
| 32 | 12285 | 1 | TRIGGER GUARD U/W |
| 33 | 12290 | 1 | CLAMP SCREW |
| 34 | 12291 | 1 | THUMB PLATE |
| 35 | 12470 | 1 | CAPSCREW |
| 36 | 12535 | 1 | CIRCUIT TYPE "E" STICKER |
| 37 | 12786 | 1 | STUD |
| 38 | 12815 | 1 | WHEEL NUT SPANNER |
| 39 | 13783 | 1 | DRIVE GEAR |
| 40 | 13789 | 1 | MOTOR CAP ASSY (INCLUDES DU BUSHING & DOWEL PIN) |

| ITEM# | PART# | QTY | DESCRIPTION |
|-------|-------|-----|--|
| 41 | 13790 | 1 | BEARING CARRIER |
| 42 | 13791 | 1 | SPINDLE SHAFT |
| 43 | 13796 | 2 | DEAD HANDLE BRKT WELDMENT |
| 44 | 13812 | 1 | ROTARY SHAFT SEAL * |
| 45 | 13813 | 1 | BALL BEARING |
| 46 | 13828 | 1 | WOODRUFF KEY #404 |
| 47 | 16495 | 1 | HUB NUT (GR2930101 ONLY) |
| 48 | 17061 | 1 | VALVE KEEPER |
| 49 | 22063 | 1 | SPOOL CAP |
| 50 | 22064 | 1 | ROD WIPER * |
| 51 | 23678 | 1 | HEADED PUSH PIN |
| 52 | 28322 | 1 | STICKER "CE" 25MM |
| 53 | 28409 | 1 | COMPOSITE STICKER |
| 54 | 28913 | 1 | DRIVE FLANGE (GR2930101 ONLY) |
| 55 | 73041 | 1 | ON/OFF VALVE SPOOL (NOTE: SEE PAGE 18 BEFORE ORDER- ING) |
| 56 | 73311 | 1 | MAIN HOUSING ASSY (INCLUDES DU BUSHING) (NOTE: SEE PAGE 18 BEFORE ORDERING) |
| 57 | 73684 | 1 | NAME TAG - GR29 UW |
| 58 | 74818 | 1 | INFORMATION TAG - GR2930101 |
| 59 | 13779 | 1 | JAM NUT (INCLUDED WITH GR29310 ONLY) |
| | 16969 | 1 | SEAL KIT |

^{*} DENOTES PART IN SEAL KIT















Contact us

29th Street, Amman Road, Behind Al Huraiz Est. For Industry, Al Qusais, Industrial Area - 1, Dubai, United Arab Emirates

: 009714 2580533

Fax: 042516664

UAE: 00971505648178

UK: 00447951966260

Website: www.synergyequipment.com

: ram@synergyequipment.com

For Sale: info@synergyequipment.com

