

THREE DIVER COMPACT AIR PANEL (BACK HIDDEN PLUMBING) SY-3DCPD023-R-XDV-XM



PART NO : SY-3DCPD023-R-XDV-XM


IMCA D023	DESIGN for Surface Oriented (Air) Diving Systems
IMCA D018	Code of Practice for The Initial and Periodic Examination, Testing and Certification of Diving Plant and Equipment




THREE DIVER COMPACT AIR PANEL (BACK HIDDEN PLUMBING) SY-3DCPD023-R-XDV-XM

Sr.	Description
1	Powder coated marine grade aluminum non rust fascia (various colors available)
2	All engraved lines with each valve/fitting/regulator clearly marked
3	DP alarm to connect to bridge with mute button (optional)

Design criteria for dive panel

1 x 0-230 fsw/70 msw Depth gauge, 6", 0.25 % accuracy, mirror scale, with calibration point , Diver 1, Color coded **Green** 

1 x 0-230 fsw/70 msw Depth gauge, 6", 0.25 % accuracy, mirror scale, with calibration point , Diver 2, Color coded **Yellow** 

1 x 0-230 fsw/70 msw Depth gauge, 6", 0.25 % accuracy, mirror scale, with calibration point , Diver 3, Color coded **Red** 

Sr.	Part Number	Description	Qty
1	SY-PRO O2	Oxygen analyzers with high low alarm (one per diver)	3
2	SY-VFA-BV-23	Flowmeters (per analyzer)	3
3	SY-873-400	Option 1 Aqua Environment high pressure Regulator w/gauges	3
4	SY-44-1315-2081-005	Option 2 Tescom high pressure regulator	3
5	SY-FLR-DS	Flow Restrictor (one per diver)	3
6	SY-DIVMKII-COM (Optional)	Interspiro full face breathing air mask, communications, 10 mtr of Communication cable with end fitting (one end to BA comms/other to chamber comms)	1
7	SY-UPS-DP (Optional)	Emergency power back – UPS for video systems	1
8	SY-PG-A-2.5-5000	High pressure gauges (incoming air supply) 0-5000 psi (Hp1)	3
9	SY-PG-A-2.5-5000	High pressure gauges (incoming air supply) 0-5000 psi (Hp2)	3
10	SY-PG-A-2.5-500	Low pressure gauge (regulated air supply) 0-500 psi	3
11	SY-PG-A-2.5-500	Low pressure gauge (common low pressure supply) 0-500 psi	3
12	SY-PG-A-2.5-500	Low pressure gauge (downstream for umbilical supply pressure)	3
13	All air supply lines (inlet and outlet) are color coded per diver		
14	Pressure gauges		
15	Diver 1 – Independent high pressure line 1 Diver 1 – Independent high pressure line 2 Diver 2 – Independent high pressure line 1		
16	Diver 2 – Independent high pressure line 2 Diver 3 - Independent high pressure line 1 Diver 3 - Independent high pressure line 2		
17	Diver 1 – Common low pressure line Diver 2 – Common low pressure line Diver 3 – Common low pressure line		
18	All tubing used will be stainless steel high pressure		
19	All valves for incoming air supplies will be brass , high pressure		
20	All valves for regulated supplies will be brass, high pressure		

THREE DIVER COMPACT AIR PANEL (BACK HIDDEN PLUMBING) SY-3DCPD023-R-XDV-XM

DIVE PANEL COMMUNICATION (Sold Separately)

Sr.	Part Number	Description	Qty
1	2830A-11	Amron 3 diver radio with ac/dc power	2
2	2405-28	Push to talk microphone	2

DIVE PANEL DIVER CCTV SYSTEMS (Sold Separately)

Sr.	Part Number	Description	Qty
1	SY-DIVERVISION SERIES	Diver 1/Diver 2 / Diver 3 , surface control unit, Synergy/Outland Technology	3
2	SY-MON-15.5-TFT	Diver 1/Diver 2 / Diver 3 , 15.5"waterproof TFT monitor	1
3	SY-DVR-1TB-HD	Primary Recorder, 1 TB hard drive (simultaneous recording of all diver)	1
4	SY-DVR-1TB-HD	Backup recorder (black box) 1 TB hard drive (simultaneous recording of all dives), USB out for recording to USB sticks, HDMI out for mirror image to be displayed remotely via HDMI cables	1

THREE DIVER COMPACT AIR PANEL (BACK HIDDEN PLUMBING) SY-3DCPD023-R-XDV-XM

SY-2830A-11 AMCOM III THREE-DIVER RECHARGEABLE PORTABLE COMMUNICATOR WITH OUTDOOR AC POWER MODULE AND INTERNATIONAL LOCKING POWER CORD



NEWLY DESIGNED ENHANCEMENTS:

High Audio Fidelity

Ultra-low noise circuit combined with noise suppression circuitry produces crystal clear speech. Automatic gain adjustment

will guard audio signal from distortion, enhance speaker protection and audio quality. Increases band width 47%.

Extended Battery Operation Time

Audio amplifier card deploys the state-of-the-art Class-D digital audio power amplifier. Has very low power dissipation, produces less heat, and extends battery life up to 32%.

Flexible Gain Settings

The audio amplifier card has adjustable gain settings to accommodate different communication applications and environments.

Ultra-Low Electromagnetic Interference (EMI)

EMI is achieved through spread-spectrum and de-phase control techniques providing for optimum integration with diving systems.

Outdoor Rated AC Power Module

Weather resistant, IP65 rated AC power entry module accommodates country specific AC power cords.

Country Specific V-Lock AC Power Cord

At time of order, simply choose the IP54 rated Locking AC power cord you need.

FEATURES:

- Separate channels and volume controls for each diver and tender to accommodate individual earphone and microphone adjustments, equipment variations and individual comfort levels.
- Divers' umbilicals can be set to 4-wire mode (full duplex) or 2-wire mode (push-to-talk) or any combination of the two modes for any diver.
- Ability to use both dynamic and pre-amplified diver microphones with a unique circuit that detects microphone type and automatically adjusts volume levels.
- Weatherproof push-to-talk microphone for better voice intelligibility topside. For optimum clarity, see Tech Note (below) for other recommended equipment.
- Internal charger allows for simultaneous charging and operation of the unit while protecting the rechargeable battery from being over-charged. Automatically supplies power to the audio amplifier when AC power is disconnected to allow for continued operation.

THREE DIVER COMPACT AIR PANEL (BACK HIDDEN PLUMBING) SY-3DCPD023-R-XDV-XM

SPECIFICATIONS:

- Input Impedance (Each Input): 250 Ohms
- Frequency Response: 300 - 10000 Hz
- Common Mode Rejection: 40 dB Minimum
- Current Drain Maximum Full Volume: 3 Amps
- Minimum Quiescent: 0.190 Amps
- Output Impedance: 4 Ohm
- Power Supply Voltage: 12 VDC Nominal (9 Volts Minimum - 16 Volts Maximum)
- AC Power Operating Range: 90-264 VAC, 50-60 Hz
- Sensitivity (Input): 0.5 mV
- Output Power (RMS @ 4 Ohm Load, 12 VDC): 10 Watts Audio
- Battery Life: 41 hours
- Dimensions: 10 in. H x 9 in. W x 14.5 in. L (25.4 cm x 22.9 cm x 36.8 cm)
- Weight: 17.05 Lbs. (7.73 Kg)

INCLUDED WITH COMMUNICATOR:

SY-2830A-11 AMCOM III Two-Diver Rechargeable Basic Portable Communicator with Outdoor Power Module and International Locking Power Cord includes:

- (1) SY-2405-28 Amron Hand-Held Push-to-Talk Microphone
- (1) SY-2890-05 Amron 12 VDC Sealed Lead Acid Gel-Cell Rechargeable Battery with Slide terminals
- (1) SY-283XA-UM Amron Three-Diver Portable Communicator User Manual

AVAILABLE OPTIONS:

- SY-2460SM-28 Amron Single Muff Operator Headset with Boom Mic and Dual Banana Plugs
- SY-2401-28 Amron Deluxe Headset with Boom Mic
- SY-2822-28 Amron Remote Walk-and-Talk (4-wire mode)
- SY-2821-28 Amron Remote Walk-and-Talk (2-wire mode)

TECH NOTE:

All communicators will inherently transfer topside noise to the divers when the tender speaks directly into the communicator's panel speaker. To eliminate background noise at the surface, use the 2405-28 Push-to-Talk Microphone, included with this model. For optimum communications, we recommend purchasing the 2401-28 Deluxe Headset with Boom Mic, topside. For tender mobility, use the 2401-28 Deluxe Headset with Boom Mic along with the 2822-28 Remote Walk-and-Talk (4-wire mode) or the 2821-28 Remote Walk-and-Talk (2-wire mode). For wireless tender communications, order the 2830A-03 Three-Diver Deluxe Portable Communicator with Wireless Tender.

CERTIFICATES PROVIDED WITH EACH THREE DIVER AIR PANEL

Diving panel	Bureau Veritas
Imca	D018 / D023
Class	Bureau Veritas pressure test witness for entire system
Fmea	As built by Synergy
Fmea stamped by class	As built by Synergy and reviewed by Class (optional)
Warranty	One year Synergy manufacturing warranty

Industry & Facilities Division
Third Party Inspection Report
Page 1 of 6

INSPECTION REPORT No. ISIA-12110-B-03 Revision No. 0

Client: W/S Strategic Diving and Equipment Solutions FZC
Product: D018, D023

Inspected Location: UAE, Industrial Area, Dubai
Inspection Reference No: ISIA-12110-B-03

MATERIAL / SUBJECT OF INSPECTION

ITEM TAG No.	QTY	QTY Inspected
Three Diver Panels	03	03

A - INSPECTION RESULT

Satisfactory (Without comments) Satisfactory with comments (List of missing parts or Non Conformity items is still open) Not Satisfactory (List of missing parts or Non Conformity items is still open)

Inspection Summary: (For information to the client)

- At the request of W/S STRATEGIC DIVING EQUIPMENT HEAD without the presence of a third party, the inspection was carried out at the site on 14th June 2024 and results were found satisfactory.
- High Pressure tests were carried out at 500 psi and low pressure (6.33) psi on all three TRITON 367.

Open Non Conformities: None Yes No

Urgent Action Items: None Yes No

Review Note Issued: Yes No

RV Satisfactory Signatures: Yes No

Industry & Facilities Division
Third Party Inspection Report
Page 3 of 6

INSPECTION REPORT No. ISIA-12110-B-03 Revision No. 0

E - INSPECTION DETAILS

E1 - Details of Witness (W) & Hold (H) Inspection Points

- Pressure test was witnessed for TRITON 367 three diver panel on 14th June 2024.
- Pressure test was witnessed for TRITON 367 three diver panel on 14th June 2024.
- Verification of Calibration Certificates for the measuring instruments and access points were found in order.

E2 - Details of Non Testing and Surveillance Points

- Visual inspection of Three Diver panel was as per procedure and found satisfactory at the time of inspection.
- Verification of calibration certificates for TRITON 367 was clearly inspected and found satisfactory.
- Final test was witnessed over three diver panels and no pressure leakage was observed and found satisfactory.
- Verification of calibration certificates for the measuring instruments were found in order.

E3 - Details of Certificate Reviews

- Calibration certificates of all measuring instruments used were verified and found satisfactory.

F - HEALTH, SAFETY & ENVIRONMENT COMMENTS
(Comment on Observations and Actions Taken During the Inspection)

- Follow proper safety procedures during inspection period and found satisfactory.

G - NON CONFORMITIES

No.	Description	Status	Responsible	Report No.	Closed on	Report No.	Comments
01							

Industry & Facilities Division
Third Party Inspection Report
Page 2 of 6

INSPECTION REPORT No. ISIA-12110-B-03 Revision No. 0

RV Inspector: V. Raju
RV Coordinator: Subhash Reddy
BY Office: Dubai
Inspection Report Date: 14.06.2024

B - REFERENCE DOCUMENTATION

Title	Reference No.	Rev.	Approved by	Date
TRITON 367 (367)	001	01	Subhash Reddy	14.06.2024

C - ATTENDERS

Name	Position	Representing
Mr. V. Raju	Inspector	Industry
Mr. Subhash Reddy	RV Coordinator	Industry
Mr. Ravi Kumar	Technical Manager	Industry

D - MEASURING & TESTING EQUIPMENT USED

Equipment Type	Equipment Identity No.	Last Calibration Date	Expiry Date
Digital Pressure Gauge	9524	30.11.2019	29.11.2020

Industry & Facilities Division
Third Party Inspection Report
Page 6 of 6

INSPECTION REPORT No. ISIA-12110-B-03 Revision No. 0

J - ATTACHMENTS

No.	Attachment Name	Total Pages	Description
1	2nd Safety Check List	0	2nd Safety Check
2	Calibration Certificate	0	Calibration Certificate
3	Calibration Certificate	0	Calibration Certificate

APPENDIX

Description: Three Diver Panel and 3rd Quad - 116
Country of Origin: USA
Manufacturer: TRITON 367
Year of Manufacture: 2024
Design Pressure: 6.33 MPa / 91.9 PSI
Test Pressure: 18.99 MPa / 274.3 PSI

Pneumatic Test Details

- Pneumatic test was witnessed for Three Diver panel (TRITON 367) on 14th June 2024.
- High pressure supplied to the panel was 5500 psi (design pressure being 3000 psi).
- Low pressure supplied to the panel was 6.33 psi (design pressure being 6.33 psi).
- Over pressure on the panel was held for 30 minutes duration, decreasing in pressure upto 5.00 psi and held for 30 minutes.
- Seem Solution test was performed on Three Diver panel and 3rd Quad 116 showing no indications of leakage and found satisfactory.


ORDERING INFORMATION

Sr.	Part Number	Description
1	SY-3DCPD023-R-3DV-3M	THREE DIVER AIR PANEL, WITH 1 X AMRON RADIOS, D1 / D2 / D3 VIDEO SYSTEMS
2	SY-3DCPD023-R-2DV-2M	THREE DIVER AIR PANEL WITH 1 X AMRON RADIOS, D1 / D2 VIDEO SYSTEMS
3	SY-3DCPD023-R-1DV-1M	THREE DIVER AIR PANEL WITH 1 X AMRON RADIOS, D1 VIDEO SYSTEMS
4	SY-3DCPD023-R	THREE DIVER AIR PANEL WITH 1X AMRON RADIOS (NO CCTV)
5	SY-3DCPD023	THREE DIVER AIR PANEL (NO RADIO , NO CCTV)

BESPOKE DESIGNS – ANY CONFIGURATION AS PER CLIENT REQUIREMENT

THREE DIVER COMPACT AIR PANEL (BACK HIDDEN PLUMBING) SY-3DCPD023-R-XDV-XM

Contact us

 29th Street, Amman Road, Behind Al Huraiz Est. For Industry,
Al Qusais, Industrial Area – 1,
Dubai, United Arab Emirates

 Tel : 009714 2580533 

 Fax : 042516664 

 UAE : 00971505648178 

 UK : 00447951966260 

 Website : www.synergiequipment.com

 Email : ram@synergiequipment.com

 For Sale : info@synergiequipment.com

