BAUER HIGH PRESSURE COMPRESSORS SY-JUNIOR

JUNIOR II

Ruggedness, reliability, a wide range of applications and its compact flexibility have made the JUNIOR a worldwide classic. With over 100,000 units sold, it has become a real bestseller around the globe.

Thanks to its small dimensions and sophisticated technology, the smallest of our portable breathing air compressors is ideal for sports divers, marine use, use for respiratory protection applications as well as paintball and shooting sports

In short: for all those who do not want to do without pure and safe breathing air in mobile applications. This lightweight and compact unit can be transported by one person - and fits in almost any car boot.

Technical Specifications:

Product Code: SY-JUNIOR-XXX

- > 100 l/min
- > 225 or 330 bar
- > 2.2 kW (4.2 kW petrol version)
- > Available with three-phase motor, single phase motor or petrol engine

























BAUER HIGH PRESSURE COMPRESSORS SY-JUNIOR

Operational Features (Selection):

- > Additional filling device for 225 or 330 bar
- > Switchover device for 330/225 bar
- > Frame and carrying handle of stainless steel (only with JUNIOR II)
- > Automatic condensate drain including automatic shutoff when final pressure is reached
- > Intake telescope (standard with OCEANUS-B and JUNIOR II-B) or intake manifold for attaching a suction hose
- > Trolley

Technical Data:

Туре	Charging Rate ¹		Operating Pressure max		Purification Number of . system Stages		Speed	Drive and Motor Power		Net Weight approx.	Dimensions L x W x H
	l/min	cfm	bar	psig			rpm	Motor	kW	kg	cm
JUNIOR II-B	100	3.5	330	4780	P 21	3	2,300	Petrol engine 4-stroke	4.2	44	79 x 37 x 44
JUNIOR II-E	100	3.5	330	4780	P 21	3	2,300	Three-phase 400 V, 50 Hz	2.2	46	69 x 39 x 44
JUNIOR II-W	100	3.5	330	4780	P 21	3	2,300	Single-phase 230 V, 50 Hz ^{3,4}	2.2	46	69 x 40 x 44
OCEANUS-B	140	5	330	4780	P 21	3	2,300	Petrol engine 4-stroke	5.1	47	77 x 38 x 44
OCEANUS-E	140	5	330	4780	P 21	3	2,300	Three-phase 400 V, 50 Hz	3	52	69 x 44 x 44
OCEANUS-W	140	5	330	4780	P 21	3	2,300	Single-phase 230 V, 50 H²	3	52	69 x 49 x 44

Note:

- 1 Measured by cylinder filling (10 l) from 0 200 bar/ 2900 psig, \pm 5%.
- 2 Plug dimension: 16 A. OCEANUS-W without plug.
- 3 Plug dimension: Schuko plug. Plug only for units with 230 V / 50 Hz.
- 4 With integrated motor protection switch (only for 220/230/240 V).












Synergy Infrastructure



BAUER HIGH PRESSURE COMPRESSORS SY-JUNIOR

Contact us

UAE • UK • INDIA • AZERBAIJAN

29th street, Amman Road, Behind Al Huraiz Est, For Industry, Al Qusais, Industrail Area - 1, Dubai, United Arab Emirates

Website: www.synergyequipment.comEmail: ram@synergyequipment.comFor Sale: info@synergyequipment.com













