

AMRON INTERNATIONAL - MASTER DISTRIBUTOR

SY-240H AMEREX MODEL HYPERBARIC WATER BASED FIRE EXTINGUISHER



Features:

- Maximum visibility during discharge
- Easy to recharge and maintain
- Leaves no powder residue
- Stored Pressure Design
- Polished Stainless Steel Cylinders
- All Metal Valve Construction
- Large Loop Stainless Steel Pull Pin
- Exclusive crevice free, butt welded cylinders

Conforms to Test Standards:

- CAN/ULC-S507 - ANSI/UL626
- CAN/ULC-S508 - ANSI/UL711

Application:

- Designed for use in manned pressure vessels/ hyperbaric chambers
- Suitable for use in chambers simulating 225 ft. (depth)

Note: Fire Extinguisher ships empty

Model 240H Hyperbaric Water Based Fire Extinguisher: Part Number Model-240H Includes:

- Fill Adapter
- Wall Hanger
- Owner's Manual

Specifications:

- Water Capacity: 2.5 gal. (9.5 liters)
- Maximum Pressure: 200 psi (13.8 bar)
- Maximum Depth: 225 FSW
- Range: 45 – 55 ft.
- Discharge Time: 55 seconds
- Dimensions: 24.5 in. H X 9 in. W X 7 in. D (62.2 cm X 22.8 cm X 17.8 cm)
- Empty Weight: 7.50 lbs. (3.40 kg)
- Temperature Range: 40°F to 120°F (4°C to 49°C)
- Relief Valve
- Outlet relief pressure: 425 PSI
- Inlet relief pressure: 3 PSI (If the fire extinguisher is empty and placed in a chamber, this valve will let pressure in from the environment into the fire extinguisher)



Contact us



29th Street, Amman Road, Behind Al Huraiz Est. For Industry,
Al Qusais, Industrial Area - 1,
Dubai, United Arab Emirates



Tel : 009714 2580533 



Fax : 042516664 



UAE : 00971505648178 



UK : 00447951966260 



Website : www.synergiequipment.com



Email : ram@synergiequipment.com



For Sale : info@synergiequipment.com

